

TELESCOPIC FLYBRIDGE CRANE 3030



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	F (mm/ inch)	G (mm/ inch)	L (mm/ inch)	Cable length (mm inch)	capacity standard (kg/lbs)	capacity optional (kg/lbs)	weight (kg/lbs)
3030/29	1750 69"	1980 78"	2600 102"	850 33"	600 24"	1560 61"	2116 85"	1425 56"	4400 173" 3500 138"	300/660	450/100 600/1320	338/740
3030/33	1860 73"	2130 84"	2890 114"	1030 41"	660 26"	1810 71"	2605 102"	1530 60"	5700 224" 4600 181"	300/660	450/100 600/1320	378/770
3030/42	2430 96"	2730 107"	3930 155"	1500 59"	950 37"	2100 83"	3260 128"	1840 73"	7700 303" 6200 244"	300/660	450/100 600/1320	440/970
3030/45	2630 104"	2930 115"	4230 167"	1600 63"	1015 40"	2250 89"	3490 137"	1965 78"	7700 303" 6200 244"	300/660	500/1100	465/1020

To choose the base, please refer to page:
 "SLEWING FLYBRIDGE CRANE BASES". Standard rotation 359°.
 * F, G dimensions are referred to installation on AL base.

