

# ELBOW CRANE 3075



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	C max (mm/inch)	D (mm/ inch)	F (mm/ inch)	G (mm/ inch)	L (mm/ inch)	$\alpha$	Cable length (mm inch)	capacity standard (kg/lbs)	weight (kg/lbs)
3075/30	1700 67"	2020 79"	2830 111"	3030 119"	920 36"	2030 80"	2060 81"	1900 75"	69°	4400 173" 3500 138"	300/700 500/1100	388/850
3075/37	1960 77"	2280 90"	3400 134"	3880 153"	1110 44"	2235 88"	2235 88"	2290 90"	69°	5700 224" 4500 177"	300/700 500/1100	434/950
3075/37.01	1960 77"	2280 90"	3350 132"	3830 151"	1060 42"	2235 88"	2820 111"	1850 73"	80°	5700 224" 4500 177"	300/700 500/1100	434/950

THIS CRANE CAN BE certified for rescue boats and can be produced in compliance with S.O.L.A.S. requirements, upon request.

ATTENTION! In case of certification request, dimensions and technical specifications may undergo significant variations.

Please contact our Technical Department for information about the available certifications for the different crane models.

Standard rotation 359°

