

THE LEGEND IS BACK!



Wide View Angle, Bright and High Definition HE-7301II / HE-7302II


10.4 inch Color LCD Echo Sounder/Plotter




HONDEX. HE-7301II /HE-7302II




Menu



PL+FF(Landscape)



PL(Landscape)



Exp+Normal(Portrait)

- Consolidated in one body for vessels where space is limited
- Quad display style (Landscape/Portrait&Reverse)
- Fast mapping using high performance CPU
- Easy setting operation with dialogic menu
- Works with C-Map NT+ or MAX
- Selection from many combination of frequency/power output suits for different types of fishing

Specifications

Display:	10.4 inch TFT Color LCD
Number of Pixels:	640x480
Dimension:	Portrait:284(H)x268(W)x152(D)mm Landscape:254.5(H)x268(W)x152(D)mm
Weight:	Approx. 4kg (excluding transducer)
◆Fish Finder Section <only HE-7301 II >	
Frequency & Power Output/Depth Range:	Please refer to below table.
Auto Range/Auto Shift:	OFF/Range/Shif
Auto Gain:	OFF/Low/High
A-Mode:	OFF/ON
Fish Alarm:	OFF/Small/Large
Water Temp. Alarm:	OFF/Within Range/Out of Range
Depth Alarm:	OFF/Within Range/Out of Range
Expansion Mode:	OFF/Bottom Lock/Auto Exp./Manual Exp.
Expansion Rate:	x2, x4, x8
Sweep Speed:	4 steps plus freeze
Background Color:	4 colors (HE-7301 II)
Color Configuration:	5 patterns(HE-7301 II)
Unit of Depth:	Meters/Feet/Fathoms/Brazas
Scale Line:	OFF/ON
Super Range:	OFF/ON
STC:	OFF/Weak/Medium/Strong
Transmitting Power:	Low/High
◆Plotter Section	
Chart Presentation:	Mercator Projection
Chart Scale:	0.005~500NM (km)
Track Display Memory Interval (Time):	1 sec., 5 sec., 10 sec., 20 sec., 30 sec., 1 min., 2 min., 5 min., 10 min., 20 min.
Track Display Memory Interval (Distance):	0.01, 0.02, 0.05, 0.1, 0.2, 0.5, 1, 2NM (km)
Color of Track Line:	7 colors (Red, Yellow, Green, Magenta, White, Cyan, Blue)
Track Display/Memory Capacity:	32,000 points
Waypoint Memory:	1,000 points
Event Mark Memory:	24,000 points
Route Memory:	20 routes
Other Functions:	Land Full Paint, Map Turning, User Self Mapping,L/L Present Position, L/L Cursor, Boat Speed & Direction, Distance & Bearing to Waypoint, Distance & Bearing to Cursor, Contour Line,Full Paint(below 100m/below 1000m/over 1000m)

Fre.(kHz)
Output(W)

Output (W)	28	32-40	50	50&200	200
600			TD22	TD48/TD47T	TD24
			0-3000	0-1500	0-1500
			0-1000	0-500	0-500
1200			TD31	TD66/TD67T	TD33
			0-3000	0-1500	0-1500
			0-1000	0-500	0-500

Output (W)	28	32-40	50	50&200	200
2500			TD70		
			0-5000		
			0-1500		
3000		TD87	TD80	TD113	TD89
		0-6000	0-5000	0-3000	0-1500
		0-2000	0-1500	0-1000	0-500

Upper: Hondex TD Type No. Middle: Depth Range (Feet) Lower: Depth Range (Meters, Fathoms, Brazas)

*Depth range does not reflect actual detectable depth.

Specification subject to change without notice.

Dealer



HONDEX is trade name of
HONDA ELECTRONICS CO.,LTD.

20 Oyamazuka,Oiwacho,
Toyohashi,Aichi,Japan 441-3193

TEL:81-532-41-2512

